

# Intelligent home guard Ip camera



Yoosee



YYP2P




Quick installation guide  
V1.1


# Mobile APP Operation Manual

## I .Two ways to download YYP2P /Yoosee APP on mobile :

### 1.For IOS :

- ① Search YYP2P /Yoosee on Apple  , download and install .
- ② Open www.yyp2p.cn or www.yoosee.co ,download IOS app.
- ③ Use QQ,Baidu,UC browser to scan QR Code on packing box .

### 2.For Android :

- ① Search YYP2P /Yoosee on  , download and install .
- ② Open www.yyp2p.cn or www.yoosee.co ,download android app.
- ③ Use QQ , Baidu , UC browser to scan QR Code of packing box .

## II .Account register

1. Open the YYP2P or YOOSEE software.
2. Click the register button (Figure 1) .
3. Select"Mobile or e-mail" (for example: if select mobile, enter your phone number then click next step, waiting for the SMS security code,then type in it,click next,then finish register and log in.)



Figure 1

## III .Device plug in (Take the Android version for example)

- 1.Put camera and mobile near WIFI router and make sure wifi signal is good,pen the wifi in you mobile and connect wireless router.(Note:not support 5G)
- 2.Power on,waiting for 30seconds until hear "du-du-du"sound  
**Tip:if you didn't hear the sound,use pin to insert the device RESET hole, press and hold for 5 seconds to hear the sword sound.After waiting 30 seconds ,you will hear "du-du-du"sound .**
- 3.After download and register,please login your YYP2P or YOOSEE in mobile(Figure 2).
- 4.Click the top right corner "+"in the device list ,enter the next step



Add local new device



Add online remote device




Scan QR code to add NVR device (only some model support)



Figure 2

5. Click "Add New Device"  ,enter the next step

6. Connection ,choose "AP Connection" 

①Choose "AP Connection",enter the next step

②Following tips,until hear the "du-du-du"sound from the device,click "hear the connect voice",enter the nest step(Figure 3)

Choose the wifi name which the phone had connected(Note:not support 5G)

input the wifi password

Establish the device new password

③Click"next" (Android)

Choose the device which need to configure network,waiting until hear "deng" sound,it means the device is connecting wifi router,when connection succeed. it will automatically enter in device list .(Note:if connection fail,delice will put off "du-du-du" sound again,mabye the device is far away from wifi router of input wrong password .)



Figure 3



Figure 4



Figure 5



Figure 6

IOS

a. as the picture show(Figure 7)

b. Click "set the WiFi"(Figure 8)

c.Choose AP hot device"start with :GM\_AP\*\*\*\*\*"(Figure 9)

d. Click the top left corner"back to YYP2P" ◀Back to YYP2P (Figure 10)



Figure 7



Figure 8



Figure 9



Figure 10

e. Waiting until hear "deng" sound, it means the device is connecting to wifi router, if connection succeed, it will enter to device list. (Note: If connection fail it may put off "du-du-du" sound again, maybe the device is far away from wifi router or the WiFi password is wrong.)

7. Smart link, Wired connection, please following the note and operate



Only add the device with pick-up, if without can't use this function



Add online device



Figure 11



Figure 12

## V, Device Preparation

1. Device in the device list

Function icon definition (Figure 12th)



Arm/Disarm



Remote playback



Device parameter settings

2. Click in the device list of the device icon, will see the live preview video icon definition in the preview interface



Preset setting



Back



Device parameter settings



Preview quality



Sound



Arm/Disarm



Full screen



Local video



Intercom



Screenshot



Figure 13

## VI. AP Mode

① Waiting 5 minutes in the configure network mode ("du-du-du" sound), it will enter AP mode automatically.

② Open "Setting", choose WLAN, find the device WiFi name (start with GW\_AP\_) and choose device name which need to connect, it will connect AP device automatically.



Figure 14



Figure 15



Figure 16

③ Open YYP2P or Yoosee in mobile and login (Figure 17th).

4 Click the device in the device list to configure network or AP mode connecting.



Figure 17



Figure 18

Click "Skip to stand-alone mode"

Click "OK" to AP preview video by connecting directly




Figure 19









Figure 20

## VI AP mode interface brief introduction

Icon definition:

-  AP mode device list
-  Added Device
-  Alarm message, local screenshot record, local video record
-  Other setting
-  More details




Figure 21

# Computer Client Operating Guide

## I . CMS download

Serve the website <http://www.yyp2p.cn> or <http://yoosee.co> (Figure 22)


click  and download it





Figure 22

## II . CMS account log in

1. There are two way for option, one is "remote loading" use the APP YYP2P or YOOSEE registered account and password to log in, no need to register again.
2. The other is "local loading", account: admin password: 00000000 (8\*0)

## III . CMS add the device

### 1.Add the local device

Click the  button in the CMS left side, would automatic search the local device, select it then click this  to the right device list, then lick "Exit" (Figure 23).

## 2. Settings




Figure 23




Figure 24




Figure 25



Figure 26

Close the picture preview, right click the device and select "Setting", then type in the password (initial password: 123) click "Ok", select "Delete" to delete the device, select "Start monitor" is for video preview, select "Standard definition" is for resolution option, select "Set IPC" is for device settings. (Figure 24, 25, 26)

### 3. Add remote device

Click "Manual adding" type the device ID, password, name, select the device group, click "Ok" then click "Quit" like the follow. (Figure 27)

**Note:** Fill in the alter password, if no change, fill in the initial one: 123




Figure 27




Figure 28

### 4. CMS video preview

To preview all the device in the list,click the device list" **Device List** " and right click it, select" **All connect** "then it would play all the device in the list,If you want to open one device,double click it then it would display the video. ((Figure 28)

## 5. Feature describe














-  Add device
-  Video preview
-  Play back
-  Record
-  Settings
-  Screen lock
-  PTZ control
-  Voice
-  PTZ panel control
-  Preview advanced
-  Preview next
-  Full screen display
-  Window display select



Figure 30



Figure 32

## CMS video record setting

### 1. CMS local video storage setting


Click this logo"  ". set the storage way and video function (Figure 29)



Figure 29






Figure 30

### 2. Manual record setting

Click the device list" **Device List** " , right click it and select" **All start record** " then all the device would take video record there,if you want to select on device,right click it and select" **Start record** ". (Figure 30)

### 3. Play back

Click the button"  " and enter the play back menu,select the record file type and pull in the list"  " , select it and enter the play site (Figure 31, 32)